

# Lumen Tech

Lighting, Inc.


## Wall Lantern Series

7" Diameter 15-5/8" Tall Flat Top Wall Mount Bollard  
Polycarbonate Lens With Internal Glass Refractor,  
Cone Reflector or Louver

### Ordering Information

Catalog Number	Watts	Light Source
<b>Internal Glass Refractor</b>		
LT14T26	26	Compact Fluorescent
LT14T32	32	Compact Fluorescent
LT14T42	42	Compact Fluorescent
LT14T57	57	Compact Fluorescent
LT1450H	50	HPS
LT1470H	70	HPS
LT14100H	100	HPS
LT1439M	39	MH
LT1450M	50	MH
LT1470M	70	MH
LT14100M	100	MH
<b>Internal Cone Reflector</b>		
LT15T26	26	Compact Fluorescent
LT15T32	32	Compact Fluorescent
LT15T42	42	Compact Fluorescent
LT15T57	57	Compact Fluorescent
LT1550H	50	HPS
LT1570H	70	HPS
LT15100H	100	HPS
LT1539M	39	MH
LT1550M	50	MH
LT1570M	70	MH
LT15100M	100	MH
<b>Internal Louver</b>		
LT16T26	26	Compact Fluorescent
LT16T32	32	Compact Fluorescent
LT16T42	42	Compact Fluorescent
LT16T57	57	Compact Fluorescent
LT1650H	50	HPS
LT1670H	70	HPS
LT16100H	100	HPS
LT1639M	39	MH
LT1650M	50	MH
LT1670M	70	MH
LT16100M	100	MH

**Cat.# BOLPC**  
Polycarbonate  
replacement lens  
fits all 7" diameter  
bollards



LT14 Internal  
Glass Refractor



LT15 Internal  
Cone Reflector



LT16 Internal  
Louver

### Specifications

**Housing:** 7" Diameter extruded aluminum with internal ballast tray for easy maintenance. See finish note.

**Housing Top:** Spun aluminum 7" diameter with a flat top. Finished same as housing.

**Wall Mount:** Cast aluminum with quick mount bracket, finished same as housing. See finish note.

**Lens:** Injection molded, 7" diameter, 1/4" thick clear polycarbonate.

**Ballast:** H.I.D. Pre-wired C.W.A., H.P.F. core and coil with capacitor. **CF** Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

**Lamp:** H.I.D. Clear medium base. **CF** PLT lamp max. 42W, 4 pin base (by others).

**Lamp Holder:** H.I.D.: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact. **CF:** White thermoplastic with snap-in lamp retainer springs.

**Finish:** Black, white, or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

**Photometric Information:** Contact factory.

**Labels:** U/L listed. Suitable for wet location.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*

***Lumen Tech***

Lighting, Inc.

**Wall Lantern Series**

**7" Diameter 15-5/8" Tall Flat Top Wall Mount Bollard  
Polycarbonate Lens With Internal Glass Refractor,  
Cone Reflector or Louver**

Contact Factory  
For  
Photometric  
Information

