

Lumen Tech

Lighting, Inc.

Lantern LED Series

Bollard Design LT

7" Diameter 41" Tall Flat Top Bollard

THINK GREEN WITH LED LIGHTING

LED's (Light Emitting Diodes) are more efficient than traditional H.I.D. (High Intensity Discharge) light sources consuming as much as 75% less energy.

H.I.D. Light sources (Metal Halide and High Pressure Sodium) are rated at 10,000 to 20,000 hours useful life. LED's are rated up to 80,000 hours providing much lower maintenance costs.

LED fixtures providing better energy efficiency and a better quality of useable light.

Specifications

Housing: Aluminum 7" diameter, fastened to a cast aluminum base with three countersunk stainless steel screws. See finish note.

Housing Top: Spun aluminum 7" diameter with a flat top. Finished same as housing.

Base: Cast aluminum, finished same as housing. See finish note.

Lens: Injection molded, 7" diameter, 1/4" thick clear polycarbonate.

Reflector: **LT6** Internal cone reflector. **LT8** Internal louver. **LT10** Internal glass refractor.

Light Source: 15W Super bright LED light engine with 120V — 277V LED driver. Available in 2700K, 3000K or 4000K color temps.

Finish: Black, white, or bronze detergent cleaned, prime coated chip resistant powder urethane polyester coating. Contact factory for other colors.

Photometric Information: Contact factory.

Labels: U/L listed. IP65 Suitable for wet location.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Catalog Number	Height	Watts	Light Source
LT615L	41"	15	Super Bright LED
LT815L	41"	15	Super Bright LED
LT1015L	41"	15	Super Bright LED



Design
LT6



Design
LT8



Design
LT10

Lumen Tech

Lighting, Inc.

Lantern LED Series

Bollard Design LT

7" Diameter 41" Tall Flat Top Bollard

**Contact Factory
For
Photometric
Information**



Anchor bolt and installation
bracket kit. Order catalog
number **AB8**.

